Jackknife and Underride Crashes in 18-Wheeler Crash Claims

Underride and jackknife crashes are two kinds of tractor-trailer collisions that frequently cause severe injuries. An underride crash happens when a smaller vehicle slides partly or completely beneath a trailer or truck body. A jackknife occurs when the tractor and trailer fold toward each other, often across several lanes. Each one raises distinct evidence questions for a truck accident attorney.

How underride happens

According to the Insurance Institute for Highway Safety (IIHS), large trucks are taller and have greater ground clearance than cars, so a lower vehicle can slide beneath a trailer, and strong underride guards can stop that from happening. When a car goes under a trailer, the trailer can strike the passenger compartment, bypassing much of the crash protection built into the front of the car.

Rear impact guards on trailers fall under Federal Motor Vehicle Safety Standards No. 223 and No. 224, found at 49 CFR 571.223 and 571.224, and 49 CFR 393.86 covers rear impact guards on trucks in service. IIHS reports that NHTSA finalized an upgraded rear guard standard in 2022. In a June 2024 report to Congress under the Bipartisan Infrastructure Law, NHTSA put the annual average at 89 deaths among light passenger vehicle occupants in two-vehicle crashes in which the passenger vehicle strikes the side of a trailer or semi-trailer and underrides it. A truck crash attorney will want to know whether the trailer had a compliant guard and what condition it was in.

How jackknife crashes happen

A jackknife usually starts with a loss of traction. State commercial driver manuals explain that locked trailer wheels make the trailer tend to swing around, and that this is more likely when the trailer is empty or lightly loaded. Hard braking, speed too fast for conditions, wet or icy pavement, out-of-adjustment brakes and shifting cargo can all contribute. Federal Motor Vehicle Safety Standard No. 121 covers air brake systems, including antilock brakes, but antilock brakes reduce wheel lockup rather than preventing every skid.

Photos of the folded rig show where the vehicles came to rest, not which unit lost control first. A tractor skid and a trailer swing can atlantatruckaccidentlawyers.wiki look similar at rest, so reconstruction relies on tire marks, ECM speed and brake data, brake adjustment readings and the load records. A semi-truck crash lawyer typically asks for the brake inspection history and the bill of lading for exactly that reason.

Rollovers and blocked lanes

FMCSA's Large Truck and Bus Crash Facts 2022 states that overturn, or rollover, was the first harmful event in 4 percent of fatal crashes involving large trucks. A jackknifed or overturned trailer can block multiple lanes, which can lead to secondary collisions with vehicles that cannot stop in time. Poor trailer visibility at night is another factor in underride cases, so investigators check the retroreflective sheeting required on many trailers under 49 CFR 393.11. A truck wreck attorney may review the police crash report and scene photos for lighting and visibility problems.

Liability and evidence in these crashes

Responsibility can extend beyond the driver: the trucking company for maintenance and training, the loader for cargo securement under 49 CFR Part 393, and the manufacturer if a guard or brake component was defective. A truck accident lawyer will usually ask that the trailer, the guard and the brake components be preserved before any repairs. Each state has its own statute of limitations and fault rules, and this general information is not legal advice or a prediction about any claim.